

Anziehvorschrift für Zylinderkopf		451.500 passend für / suitable for adaptable à / adaptable a Hyundai	 Das Original
Tightening Instructions for Cylinder Head			
Instructions de serrage pour culasse			
Prescripciones de apriete para culatas			
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete	
⑧ ④ ① ⑤ ⑨ ⑦ ③ ② ⑥ ⑩			
Anziehen/ Tightening/ Serrage/ Apriete	* ➤ ➤	32 Nm 64 Nm 120° 120°	
Zeichenerklärung / Explanations / Explication / Explicacion			
* ★ ☐ ● ➤	neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro
Motortyp / Engine type / Type de moteur / Tipo de motor			
Ø: 88,5 mm; ⅜: 1,1 mm			
Mot: D4EB 2,2 ltr. 110-114 kW (150-155 PS)			
Grandeur 2006- Santa Fé 2005-			
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601		*451.500*	